


KLS-25M

Mini Size Optical Light Source




Product Characteristics


- 2.5mm universal
- Typical output power: $\geq 5\text{dBm}$
- Wavelength: 1310/1550nm
- Drop protection: 2m
- Low battery reminder function
- Water-resistant keys
- Pocket size design
- LED lighting, clear in the dark environment




Backlight display



One-key start



Automatic shutdown



Plug and play



Super long standby



Silicone protective case

Modulation Carrier Output

Continuous output, three modulation frequencies

270Hz

1000Hz

2000Hz



Singlemode

1310nm+1550nm



Main Features



Drop protection



Mini Size



Detachable protective sleeve




LED lighting

KLS-25M




FC



SC



LC(Optional)



ST

Wavelength(nm)	1310/1550nm
Typical Output Power	≥-5dBm
Optical Connector	2.5mm universal (1.25mm for LC is Optional)
Power Supply	Alkaline Battery(2 AAA 1.5V batteries)
Output Stability	±0.05dB/15mins; ±0.1dB/ 8h
Modulation Frequencies	CW, 270Hz, 1KHz, 2KHz
Dimensions / Weight	130x65x35mm / 180g

Product Display



HEAD OFFICE

KomShine Technologies Limited

CONTACT US

Add: 2F Bldg. D Qinsheng Tech. Pk. Nanjing, JS, 210001, China

TEL: +86 (025) 66047688

Web: www.KomShine.com

Mail: info@komshine.com

* Komshine reserves the right to improve, enhance, or modify the features and specifications of KomShine products without prior notification.

*Company and product names appearing in this catalogue are registered marks or trademarks of respective companies.

* This catalogue is printed using environmentally friendly paper and ink.