

# KPM-25m

Mini Power Meter



## Product Feature

- 2.5mm universal interface
- Accuracy:  $\pm 0.2\text{dB}$
- Wavelength: 850~1625nm
- Range of measurement:  $-70\sim+6\text{ dBm}$  /  $-50\sim+26\text{dBm}$
- Manual calibration
- Waterproof button suitable for different outdoor environment
- Mini case protection design, compact & generous
- LED lights, suitable for dark environment



Backlight display



One key start



Auto power-off



Resolution: 0.01dB



7 Wavelengths detection



Silicon protection pad

## Product Characteristics



Drop resistance



Compact



LED light



Separate protective jacket

# KPM-25m



SC



FC



ST



LC(Optional)

Wavelength (nm)	850/980/1300/1310/1490/1550/1625nm
Measurement range (dBm)	-70~+ 6 dBm / -50~+26dBm
Optical connector	2.5mm universal interface
Power supply	Alkaline Battery(2 AAA 1.5V batteries)
Resolution (dB)	0.01
Operating temperature	-10~+60(°C)
Storage temperature	-25~+70(°C)
Dimension / Weight	137x60x37mm / 180g

## Product Display



### HEAD OFFICE

KomShine Technologies Limited

### CONTACT US

Add: 2F Bldg. D Qinheng Tech. Pk. Nanjing, JS, 210001, China

TEL: +86 ( 025 ) 66047688

Web: [www.KomShine.com](http://www.KomShine.com)

Mail: [info@komshine.com](mailto:info@komshine.com)

\* Komshine reserves the right to improve, enhance, or modify the features and specifications of KomShine products without prior notification.

\* Company and product names appearing in this catalogue are registered marks or trademarks of respective companies.

\* This catalogue is printed using environmentally friendly paper and ink.