


KPM-35

High precision optical power meter



Product Features

- 2.5mm universal interface+SC
- ± 0.2 dB accuracy
- Wavelengths 850–1625nm
- Measurement range $-70\sim+10$ dBm/ $-50\sim+26$ dBm
- Manual calibration
- Waterproof keys suitable for various outdoor environments
- Silicone jacket, anti-drop 2m
- LED lights, suitable for dark environment



Backlit display



One key start



Automatic shutdown



Resolution 0.01 dB



7 Wavelengths detection



Silicone protective jacket

Product Characteristics



Anti-fall



Compact



LED lights



Split protective jacket

KPM-35



SC



FC



ST



LC(Optional)

Wavelengths(nm)	850/980/1300/1310/1490/1550/1625nm
Measurement Range	-70~+10dBm/-50~+26dBm
Optical Connector	2.5mm universal interface + SC
Power Supply	Alkaline battery (3AA 1.5V battery)
Resolution (dB)	0.01
Working Temperature	-10~+60(°C)
Storage Temperature	-25~+70(°C)
Dimensions/Weight	160x85x45mm / 220g



Product Display



HEAD OFFICE

KomShine Technologies Limited

CONTACT US

Add: 2F Bldg. D Qinheng Tech. Pk. Nanjing, JS, 210001, China

TEL: +86 (025) 66047688

www.komshine.com

ventas@komshine.com

* Komshine reserves the right to improve, enhance, or modify the features and specifications of KomShine products without prior notification.

* Company and product names appearing in this catalogue are registered marks or trademarks of respective companies.

* This catalogue is printed using environmentally friendly paper and ink.