

KFI-35

Optical Fiber Identifier



Features & Applications

- Display relative optical power.
- Test online without interruption of the link.
- Recognize the signal of 270Hz, 1KHZ,2KHZ.
- Comes with a hood to provide more accurate test results outdoors.
- Identify the propagation direction of light, sound alarm reminder.
- LED display, 4 fixtures support bare fiber, 0.9mm, 2mm, 3mm fiber.
- Test sensitivity -40dBm to 10dBm.
- Low power reminder.

4-IN-1 Holder



3
MM



250
µm



2
MM



900
µm



Bare fiber cable



0.9mm fiber cable



ftth drop cable



3.0mm jump cable

SPECIFICATIONS:

Type	KFI-35
Identified Wavelength Range	800nm to 1700nm
Identified Signal Type	CW,270 Hz ± 5%,1 kHz ± 5%,2 kHz ± 5%
Detector Type	φ1mm InGaAs 2 pcs
Adapter Type	φ0.25(for Bare Fiber),φ0.9,φ2.0(Applicable for φ3.0Cable)
Signal Direction	Left & Right LED
Optical Power Reading	-40 dBm to 10 dBm
Signal Frequency	270Hz,1kHz,2kHz
Power Supply	AA*2
Operating Temperature	-10°C to 60°C
Storage Temperature	-25°C to 70°C
Dimension	195mm*10mm*8mm
Weight	235g

PRODUCT LIST:



CONTACT US:

KomShine Technologies Limited

HEAD OFFICE:

2F Bldg. D Qinhen Tech. Pk. Nanjing, JS, 210001, China

TEL: +86 25 66047688

www.komshine.com

ventas@komshine.com

- * Komshine reserves the right to improve, enhance, or modify the features and specifications of KomShine products without prior notification.
- * Company and product names appearing in this catalogue are registered marks or trademarks of respective companies.
- * This catalogue is printed using environmentally friendly paper and ink.